



STANDARD BRACKETS

Standard Workstation and Countertop Brackets



- 1- 1/2" forms with multiple 1/4" mounting holes per side. (mounting hardware not included)
- Made of 1/8' steel.
- The 10 larger sizes have a 3" x 3" 45-degree notch that allows for wall cleat and wire run clearance.
- Very strong: load limit range of 1420 lbs to 2920 lbs per pair.
- Reversible design makes brackets versatile & easy to use.
- Available in Almond, Black, Brown, Grey, Primed and White.
- SOLD PER PAIR Packaged in equal quantities of lefts and rights.

Stocked Sizes - Sold Per Pair (1 left | 1 right)

★ 5" x 8"	★ 18" x 18"
★ 8" x 12"	★ 18"x 24"
★ 12" × 12"	★ 21" × 21"
* 12" x 18"	★ 24" x 24"
★ 15" x 15"	★ 24" x 29"
★ 15" x 21"	29" x 35"

★IN-STOCK BLACK & WHITE





STANDARD BRACKETS

ALUMINUM BRACKETS



- Brushed aluminum finish with a clear powder coat.
- 1061-H24 Aluminum.
- 2 Gauge. (.25" thickness)
- 1-1⁄2" forms with 1⁄4" mounting holes.
- Load limit range of 1200 lbs to 2200 lbs per pair.

<u> Available Sizes - Sold Per Pair (1 left | 1 right)</u>

5" x 8"	12" x 18"
8" x 12"	15" x 15"
12" x 12"	15" x 21"

18" x 18"	24" x 24"
18"x 24"	24" x 29"
21" x 21"	29" x 35"

STAINLESS STEEL BRACKETS



•	Brushed finish with a powder coat
	clear coat.

- 304 Stainless Steel.
- 12 Gauge. (.110 thickness)
- 1-1/2" forms with 1/4" mounting holes.
- Load limit range of 1020 lbs to 1450 lbs per pair.

<u> Available Sizes - Sold Per Pair (1 left | 1 right)</u>

8" x 12" 12" x 18"

15"	Х	21"
18"	Х	18"

18" x 24" 24" x 29"





CONCEALED BRACKETS

U.S. MADE CONCEALED BRACKETS



- Load limit range of 1,830 lbs. to 4,520 lbs. per pair.
- Mounting hardware included. (3/8" 16 x 3" carriage bolt assemblies)
- All welds on reverse for easy, clean install.
- Available in Black powder coat only.
- Recommend backing when used with metal studs.

<u>Available</u>	Sizes - Sold Per	<u>Pair (unive</u>	<u>rsal bracket)</u>
US C - 9"	US C - 12"	US C - 18"	US C - 24"

STANDARD CONCEALED BRACKETS



- C and EC Brackets available in 2.0" or 1.0" versions.
- Load limit range of 1800 lbs to 7960 lbs per pair.
- Mounting hardware included. (3/8"-16 X 3 bolt assemblies)
- All welds on reverse for easy, clean install.
- Stocked in Black & White.

Available Sizes - Sold Per Pair (universal bracket)

C(1.0) - 9" C(1.0) - 12" C(1.0) - 15"

C(1.0) - 18"

- *****C(2.0) 9" *****C(2.0) - 12"
- ★C(2.0) 15"
- *****C(2.0) 18"
- ★C(2.0) 21" ★C(2.0) - 24"
- (2.0) = 24
- 15" C(2.0) 30"

★IN-STOCK BLACK & WHITE





CONCEALED BRACKETS

EXTENDED CONCEALED BRACKETS

	JAAONETO		
 C and EC Brackets are available in 2.0" or 1.0" versions. Load limit range of 1800 lbs to 7960 lbs per pair. Upper extension (EC) provides superior strength. Mounting hardware included. (3/8"-16 X 3 bolt assemblies) All welds on reverse for easy, clean install. Select Sizes Stocked in Black & White. 			
<u>Available Size</u>	<u>es - Sold Per Pair</u>	<u>(universal bracket)</u>	
EC(1.0) - 9"	EC(2.0) - 9"		
EC(1.0) - 12"	* EC(2.0) - 12"	★EC(2.0) - 21"	
EC(1.0) - 15"	★ EC(2.0) - 15"	EC(2.0) - 24"	
EC(1.0) - 18"	★ EC(2.0) - 18"	EC(2.0) - 30"	
FLAT EXTENDED CONCEA	()		
 Upper extension provides superior strength. Load limit range of 1100 lbs. to 4900 lbs. per pair. Mounting hardware included. 3/8" - 16 x 3 bolt assemblies for 2.0 Brackets. 3/4" - 16 x 3" bolt assemblies for 1.0 Brackets. All welds on reverse for easy, clean install. Half Inch, horizontal support arm, can be completely concealed. Select Sizes Stocked in Black & White. 			
<u>Available Sizes - Sold Per Pair (universal bracket)</u>			
ECFLAT(1.0) - 9"	★ECFLAT(2.0) - 9	"ECFLAT(2.0) - 21"	
ECFLAT(1.0) - 12"	ECFLAT(2.0) - 12	*ECFLAT(2.0) - 24"	
ECFLAT(1.0) - 15"	★ECFLAT(2.0) - 15	$\sum_{i=1}^{n} \sum_{i=1}^{n} \sum_{j=1}^{n} \sum_{j=1}^{n} \sum_{j=1}^{n} \sum_{i=1}^{n} \sum_{i=1}^{n} \sum_{i=1}^{n} \sum_{j=1}^{n} \sum_{i=1}^{n} \sum_{i$	
ECFLAT(1.0) - 18"	* ECFLAT(2.0) - 18	3"	
★ IN-STOCK BLACK & WHITE			





★CFLAT(2.0) - 21"

★CFLAT(2.0) - 24"

CONCEALED / ADA BRACKETS

FLAT CONCEALED BRACKETS

- Load limit range of 1100 lbs. to 4900 lbs. per pair.
- Mounting hardware included.
- 3/8" 16 x 3 bolt assemblies for 2.0 Brackets.
- ¼" 16 x 3" bolt assemblies for 1.0 Brackets.
- All welds on reverse for easy, clean install.
- Half Inch, horizontal support arm, can be completely concealed.
- Select Sizes Stocked in Black & White.

Available Sizes - Sold Per Pair (universal bracket)

CFLAT(1.0) - 9" CFLAT(1.0) - 12" CFLAT(1.0) - 15" CFLAT(1.0) - 18" ADA BRACKETS



★ADA-23 W/ HOLES★ADA-23 W/O HOLES★ADA-21 W/ HOLES

- Available with a 21" or a 23" top.
- Select sizes stocked in Black & White.
- 12 Gauge Steel offers superior strength.
- Optional mounting holes on sides of <u>Black ONLY</u> Brackets to install your finishing panel if desired.
- ADA(21) accommodates 22" to 24" tops.
- ADA(23) accommodates 24" to 26" tops.
- Spring clips & screws provided for easy on/off skirt attachment.
- No visible fasteners.
- No tools required to remove & reinstall skirt.
- Mounting holes provided for the skirt if you do not wish to use spring clips.
- 3x3 cut out for wall cleat & wire run clearance.
- Packaged 2 per box.

★IN-STOCK





HYBRID BRACKETS

STANDARD HYBRID BRACKETS

	 Hybrid brackets available in a 1.5" or a 1.0" version.
1	• Multiple 1/4" mounting holes. (hardware not included)
	 1/8" steel construction.
	 Very strong: load limit range of 400 lbs to 2200 lbs
	depending on version and support arm length.
	Finishing caps provided.
	• Very versatile. Can be used as Standard Mount or
	Concealed Mount.
-	

• Select Sizes in Stock in Black & White.

<u>Available Sizes - Sold Per Pair (universal bracket)</u>

- HYB(1.0) 9" HYB(1.0) - 12" HYB(1.0) - 18" HYB(1.0) - 21" HYB(1.0) - 24"
- *****HYB(1.5) 9" *****HYB(1.5) 12" *****HYB(1.5) 15" *****HYB(1.5) 18" *****HYB(1.5) 21" *****HYB(1.5) 24"

HEAVY DUTY HYBRID BRACKETS



- 18" Tall x 18" or 24" projection x 3" wide.
- Load Limits: 1700 lbs per pair 18", 1350 lbs per pair 24".
- Recommend double studs for installation.
- Finishing caps provided.
- Available in Black & White.

★ IN-STOCK BLACK & WHITE





FLOATING VANITY BRACKETS

- Available in <u>White only.</u>
- 2" Tall x 28" Wide x ¼" Thick.
- 18" Support Arm Projection.
- 1100 lb Load limit.
- Blocking recommended across the back plate.
- One bracket per box must buy two for a pair.

HIDDEN SHELF BRACKETS

- Available in <u>White only.</u>
- 1.5" tall x 20" wide x .25" thick.
- 450 lbs/pr 6", 400 lbs/pr 9" and 350 lbs/pr 12".
- Blocking across the back plate is recommended.
- Brackets can be hidden in a boxed shelf.
- One bracket per box must buy two for a pair.







FLOATING SHELF BRACKETS



- Available and stocked in white.
- 1.75" tall x 1.5" wide x .25" thick.
- 2000 lbs/pr 6", 1500 lbs/pr 9" and 1000 lbs/pr 12".
- Brackets must be mounted directly to the stud for maximum strength.
- Brackets can be hidden in a boxed shelf.
- Packaged 2 per box.

★ IN-STOCK WHITE













ISLAND & STAIR TREAD BRACKETS

ISLAND / BAR BRACKETS



- Two-part system for added strength.
- One size mounting bracket with hardware included.
- Three bar lengths available.
- Bars are 1/2" thick steel and 2" wide.
- Bars have multiple countersunk mounting holes for easy customization.
- Load limit range of 350 lbs to 3250 lbs.
- Ideal for island or bar applications.

Available Sizes - Black Only

ISLBRKT (vertical mounting bracket) ISLBAR15 - 15" bar ISLBAR34 - 34" bar ISLBAR40 - 40" bar

STAIR TREAD BRACKET



- Black powder-coated metal.
- Heavy-duty support for industrial-style design treads
- It can be mounted in either direction.
- 10 inch by 2 inch support, 1/4" thick, 1/4" mounting holes.

ST-10





NEW BRACKETS SURFACE MOUNTED FLAT BRACKETS



- Load Limit per pair 500-2000lbs.
- A simple, strong and attractive alternative for floating shelves.
- Black powder-coated metal.
- ¹/₂" thick material with ¹/₄" mounting holes.
- 4 sizes available: 6" 9" 12", and 15".
- Also available in Stainless steel and Aluminum, both brushed with clear finish.**Special Order

Available Sizes - Sold Per Pair (universal bracket)

★SF6	SF6 SS	SF6 AL
SF9	SF9 SS	SF9 AL
* SF12	SF12 SS	SF12 AL
* SF15	SF15 SS	SF15 AL

CLEAT SUPPORT BRACKET



- Black powder-coated metal.
- Countertop support for side walls and along the back edge.
- Countertop attachment holes offset with wall holes at 8 inch intervals.
- 1/4" thick, 1/4" mounting holes.
- 3 sizes available, 28", 44", and 90".

<u> Available Sizes - Sold Each</u>

CLT28

CLT44

CLT90






NEW BRACKETS

HEAVY DUTY ADJUSTABLE SUPPORT BRACKETS



- A simple, strong and adjustable support bracket.
- Available in Black(909-58) or White(933-58).
- Specify Vertical Arm + Selected Horizontal Arm Length.



<u>Vertical Arm</u>

- Available in Black(909-58) or White(933-58).
- Junction Blocks provided to us multiple Vertical Arms in succession.
- Horizontal Arms can span 2 Vertical Arms for maximum adjustability.
- Finishing Caps provided.

Horizontal Arm

- Available in Black (909-58) or White (933-58).
- Available with a 12" or an 18" Arm.
- 12" arm rated at 2400 lbs/pair.
- 18" arm rated at 1900 lbs/pair.

<u>Available Sizes - Sold Per Pair (universal bracket)</u>

ADJVA - Vertical Arm ADJHA12 - 12" Arm ADJHA18 - 18" Arm

PG.10